



HAND PALLET TRUCK OPERATORS MANUAL



2995 CLAY PIKE RILLTON, PA 15678 724-446-2000 1-800-868-5438



Fax: 724-446-0988 sales@herwin.biz www.palletsmith.com



HAND PALLET TRUCK WARRANTY

Palletsmith® by Herwin, Inc. will guarantee this product against material and manufacturing defects provided the pallet truck has been used under normal conditions.

STANDARD (3" lowered height)
LOW PROFILE (2" & 1-3/4" lowered height)

Palletsmith® will provide replacement parts for those deemed defective by **Palletsmith®**. The hydraulic pump assembly is covered for 24 months. Chassis and associated components, including handle are covered for 12 months. Wearable parts such as wheels, rollers, bushings, and bearings are covered for 6 months. Warranty begins from date of sale to the ultimate user.

HEAVY DUTY, GALVANIZED & STAINLESS STEEL

All components are covered for 6 months.

Warranty includes parts only and does not cover labor or miscellaneous costs involved in replacement of parts deemed to be defective by **Palletsmith**[®].

Bent, twisted, or misaligned forks are signs of abuse and are not covered under warranty.

Pallet trucks operating under adverse conditions such as fish, meat, or poultry processing plants, freezer application, or wet environments, including bleach wash downs or salt spray are not covered under warranty. Premature wearing of components because of lack of lubrication is not covered under warranty.

To claim warranty, please call 1-800-868-5438 or email sales@herwin.biz with model number, serial number, date of purchase and nature of problem.

SAFETY PROCEDURES



- ✔ Please read and understand the operation and safety manual before operating this pallet truck.
- ✓ Never exceed the rated capacity of this hand pallet truck and always distribute the loads evenly over the width and length of the forks.
- ✓ Never pick up a load with only one fork or try to position the load with only the fork tips.
- ✓ Never put your hands or feet under or between the pallet truck frame assembly. Always wear safety shoes when operating this equipment.
- ✓ Do not allow pallet truck to "shock load" by dropping from one level to another.
- ✓ Make sure length of pallet truck forks match the length of the pallet. It is critical that the rollers drop between the pallet bottom boards.
- ✔ Hand pallet trucks are intended to be operated on hard and flat surfaces.
- ✓ Hand pallet trucks are not to be used by an operator that is not physically capable of safely maneuvering the hand pallet truck with the load.
- ✓ Like any other mechanical equipment, hand pallet trucks should be lubricated and inspected periodically (at least every six months) for loose or missing components. Report an unsafe pallet truck to your supervisor and DO NOT operate unsafe equipment.
- ✓ Medium grade hydraulic oil is recommended except when used below 32 degrees, then use Shell Tellus V32 oil or equivalent.

TROUBLESHOOTING PROCEDURES

Condition	Cause	Remedy
Pump does not lift load	Air in the hydraulic system	Hold control lever in lowering position and pump handle 6-8 times
Lifting, neutral or lowering not engaging	Adjusting nut out of adjustment	Turn adjusting nut on control rod assembly (Item #6) until truck does not raise or lower in neutral position
Forks raise and lower with each stroke of pump handle	Dirt or debris in pump valving	Shock pump by lifting pallet truck off ground and dropping sharply away from feet. Hold control lever in lowering position and pump handle 6-8 times.
Pump does not lift to complete raised height	Low on oil due to leakage	Add hydraulic oil. Place truck in lowered position, remove plug bolt (Item # 13) Add hydraulic oil to plug bolt level. Reinstall plug bolt
Forks are not lowering completely	Debris in load wheels or linkage is out of adjustment or binding	Remove debris. Inspect linkage and front roller assembly for ease of movement. Adjust pushrod for equal fork movement if necessary. Retighten loose componentry.




PS-Series STANDARD 3" LOW. HGT.

	DTA	

ITEM NO.	DESCRIPTION	ITEM NO.	DESCRIPTION
1	Handle Cap	30	Roller
2	Control Lever	31	Split Pin
3	Split Pin	32	Safety Valve Spindle
4	Spring	33	Safety Valve Spring
5	Ball	34	Adjusting Bolt
6	Control Rod Assembly	35	O-Ring
	(includes rod, chain,	36	Screw
	adjustment bolt &	37	Spring
	adjustment nut)	38	Release Pin
7	Complete Handle	39	O-Ring
	Assembly	40	O-Ring
8	Handle Bolt (includes	41	Release Pin Nut
	washer)	42	Washer
9	Handle Bracket Bolt	43	Steer Wheel with Bearings
10	Handle Bracket Bolt		(available in poly on steel,
	Bushing		steel, poly on nylon or
11	H-Bracket		white nylon)
12	Lift Piston Ball	44	Snap Ring
13	Plug Bolt (includes	45	Split Pin
	washer)	46	Thrust Bearing
14	Pump Piston	47	Thrust Bearing Washer
15	Handle Return Spring	48	Thrust Bearing Retaining
16	Pump Piston Seal		Ring
17	Pump Piston Wiper Ring	49	Steer Wheel Axle
18	Main Lift Piston	50	New Style Pump Assembly
19	Top Seal (Wiper Ring)		(handle not included)
20	Upper Seal (Energized	51	Seal Kit (includes #16,
	Seal)		#17, #19, #20, #21)
21	Main Seal	52	New Style Valve Kit
22	Screw		(includes #22, #23, #24,
23	Seal Washer		#25, #26, #27, #37,
24	Spring		#38, #39, #40, #41)
25	Valve Spindle	53	New Style Safety Valve Kit
26	Cone Valve		(includes #32, #33, #34,
27	Ball		#35, #36)
28	Release Lever		
29	Split Pin		

PS-Series Pump Diagram STANDARD 3" LOW. HGT.






PS-Series STANDARD 3" LOW. HGT.

	FRAME DIAGRAM
ITEM NO.	DESCRIPTION
1	Screw
2	Torsion Bar with Bushings
3	Torsion Bar Bushing
4	Grease Fitting
5	Thrust Plate Shoulder Bolt
6	Thrust Plate Shoulder Bolt Bushing
7	Thrust Plate
8	Eye Bolt Pin
9	Split Pin
10	Bulkhead Pin
11	Split Pin
12	Eye bolt and nut
13	Pushrod
14	Bushing
15	Axle Bolt
16	Axle Sleeve
17	Axle Nut
18	Load Roller Axle (includes bolt, sleeve & nut)
19	Load Roller with Bearings (available in poly on steel, steel, poly
	on nylon or white nylon)
20	Washer
21	Lever Arm Assembly with bushings
22	Bushing
23	Exit Roller with Bushings
24	Split Pin
25	Fork Pin

PS-Series Frame Diagram STANDARD 3" LOW. HGT.






PSM-SeriesLOW PROFILE 2" LOW. HGT.

PUMP DIAGRAM **ITEM ITEM** NO. **DESCRIPTION** NO. **DESCRIPTION** Handle Cap 30 Roller 1 2 Control Lever 31 Split Pin 3 Split Pin 32 Safety Valve Spindle Safety Valve Spring 33 4 Spring 5 Adjusting Bolt Ball 34 6 Control Rod Assembly 35 O-Ring (includes rod, chain, Screw 36 adjustment bolt & 37 Spring Release Pin adjustment nut) 38 Complete Handle 7 39 O-Ring Assembly 40 O-Ring Handle Bolt (includes Release Pin Nut 8 41 42 Washer washer) Handle Bracket Bolt Steer Wheel with Bearings 9 43 10 Handle Bracket Bolt (available in poly on steel, Bushina steel, poly on nylon or H-Bracket white nylon) 11 12 Lift Piston Ball 44 Snap Ring Plug Bolt (includes 45 Split Pin 13 46 Thrust Bearing washer) Thrust Bearing Washer 14 Pump Piston 47 48 15 Handle Return Spring Thrust Bearing Retaining 16 Pump Piston Seal Rina Pump Piston Wiper Ring Steer Wheel Axle 17 49 18 Main Lift Piston 50 New Style Pump Assembly (handle not included) 19 Top Seal (Wiper Ring) Upper Seal (Energized Seal Kit (includes #16, 20 51 Seal) #17, #19, #20, #21) Main Seal 52 New Style Valve Kit 21 22 Screw (includes #22, #23, #24, #25, #26, #27, #37, Seal Washer 23 #38, #39, #40, #41) 24 Spring Valve Spindle 25 53 New Style Safety Valve Kit Cone Valve (includes #32, #33, #34, 26 27 Ball #35, #36) Release Lever 28

Split Pin

29

PSM-Series Pump Diagram LOW PROFILE 2" LOW. HGT.






PSM-SeriesLOW PROFILE 2" LOW. HGT.

	FRAME DIAGRAM
ITEM NO.	DESCRIPTION
1	Screw
2	Low Profile Torsion Bar with Bushings
3	Torsion Bar Bushing
4	Grease Fitting
5	Thrust Plate Shoulder Pin
6	Thrust Plate Shoulder Bolt Bushing
7	Low Profile Thrust Plate
8	Eye Bolt Pin
9	Split Pin
10	Bulkhead Pin
11	Split Pin
12	Eye bolt and nut
13	Pushrod
14	Bushing
15	Axle Bolt
16	Axle Sleeve
17	Axle Nut
18	Load Roller Axle (includes bolt, sleeve & nut)
19	Load Roller with Bearings (available in steel or poly on steel)
20	Washer
21	Low Profile Lever Arm Assembly with bushings
22	Bushing
23	Exit Roller
24	Split Pin
25	Fork Pin

PSM-Series Frame Diagram LOW PROFILE 2" LOW. HGT.





PSU-Series ULTRA LOW 1-3/4" LOW. HGT.

	ULIKA LOW		
	PUMP D	IAGRAM .	
ITEM NO.	DESCRIPTION	ITEM NO.	DESCRIPTION
1	Handle Cap	30	Roller
2	Control Lever	31	Split Pin
3	Split Pin	32	Safety Valve Spindle
4	Spring	33	Safety Valve Spring
5	Ball	34	Adjusting Bolt
6	Control Rod Assembly	35	O-Ring
	(includes rod, chain,	36	Screw
	adjustment bolt &	37	Spring
	adjustment nut)	38	Release Pin
7	Complete Handle	39	O-Ring
	Assembly	40	O-Ring
8	Handle Bolt (includes	41	Release Pin Nut
	washer)	42	Washer
9	Handle Bracket Bolt	43	Steer Wheel with Bearings
10	Handle Bracket Bolt		(available in poly on steel,
	Bushing		steel, poly on nylon or
11	H-Bracket		white nylon)
12	Lift Piston Ball	44	Snap Ring
13	Plug Bolt (includes	45	Split Pin
	washer)	46	Thrust Bearing
14	Pump Piston	47	Thrust Bearing Washer
15	Handle Return Spring	48	Thrust Bearing Retaining
16	Pump Piston Seal		Ring
17	Pump Piston Wiper Ring	49	Steer Wheel Axle
18	Main Lift Piston	50	New Style Pump Assembly
19	Top Seal (Wiper Ring)		(handle not included)
20	Upper Seal (Energized	51	Seal Kit (includes #16,
	Seal)		#17, #19, #20, #21)
21	Main Seal	52	New Style Valve Kit
22	Screw		(includes #22, #23, #24,
23	Seal Washer		#25, #26, #27, #37,
24	Spring		#38, #39, #40, #41)
25	Valve Spindle	53	New Style Safety Valve Kit
26	Cone Valve		(includes #32, #33, #34,
27	Ball		#35, #36)
			· '


Split Pin

Release Lever

28

29

PSU-Series Pump Diagram ULTRA LOW 1-3/4" LOW. HGT.






PSU-Series ULTRA LOW 1-3/4" LOW. HGT.

	FRAME DIAGRAM
ITEM NO.	DESCRIPTION
1	Screw
2	Ultra Low Torsion Bar with Bushings
3	Torsion Bar Bushing
4	Grease Fitting
5	Thrust Plate Shoulder Pin
6	Thrust Plate Shoulder Bolt Bushing
7	Ultra Low Thrust Plate
8	Eye Bolt Pin
9	Split Pin
10	Bulkhead Pin
11	Split Pin
12	Eye bolt and nut
13	Pushrod
14	Bushing
15	Axle Bolt
16	Axle Sleeve
17	Axle Nut
18	Load Roller Axle (includes bolt, sleeve & nut)
19	Steel Roller with Bearings
20	Washer
21	Ultra Low Lever Arm Assembly with bushings
22	Bushing
23	Split Pin
24	Fork Pin

PSU-Series Frame Diagram ULTRA LOW 1-3/4" LOW. HGT.






PSH Series HEAVY DUTY 3-1/4" LOW HGT.

PUMP DIAGRAM			
ITEM		ITEM	
NO.	DESCRIPTION	NO.	DESCRIPTION
1	Handle Cap	30	Roller
2	Control Lever	31	Split Pin
3	Split Pin	32	Safety Valve Spindle
4	Spring	33	Safety Valve Spring
5	Ball	34	Adjusting Bolt
6	Control Rod Assembly	35	O-Ring
	(includes rod, chain,	36	Screw
	adjustment bolt &	37	Spring
	adjustment nut)	38	Release Pin
7	Complete Handle	39	O-Ring
	Assembly	40	O-Ring
8	Handle Bolt (includes	41	Release Pin Nut
	washer)	42	Washer
9	Handle Bracket Bolt	43	Steel Steer Wheel with
10	Handle Bracket Bolt		Bearings
	Bushing	44	Snap Ring
11	H-Bracket	45	Split Pin
12	Lift Piston Ball	46	Thrust Bearing
13	Plug Bolt (includes	47	Thrust Bearing Washer
	washer)	48	Thrust Bearing Retaining
14	Pump Piston		Ring
15	Handle Return Spring	49	Steer Wheel Axle
16	Piston Nut w/ O-Ring	50	New Style Heavy Duty
17	Seal		Pump Assembly (handle
18	Main Lift Piston		not included)
19	Top Seal (Wiper Ring)	51	Heavy Duty Seal Kit
20	Upper Seal (Energized		(includes #17, #19, #20,
	Seal)		#21)
21	Main Seal	52	New Style Heavy Duty
22	Screw		Valve Kit (includes #22,
23	Seal Washer		#23, #24, #25, #26,
24	Spring		#27, #37, #38, #39,
25	Valve Spindle		#40, #41)
26	Cone Valve	53	New Style Heavy Duty
27	Ball		Safety Valve Kit (includes
28	Release Lever		#32, #33, #34, #35, #36)
29	Split Pin		

PSH-Series Pump Diagram HEAVY DUTY 3-1/4" LOW. HGT.




- (50) Heavy Duty Pump Assembly (Handle Not Included)
- 52 Heavy Duty Valve Kit
- (51) Heavy Duty Seal Kit
- (53) Heavy Duty Safety Valve Kit



PSH-Series HEAVY DUTY 3-1/4" LOW HGT.

	FRAME DIAGRAM
ITEM NO.	DESCRIPTION
1	Screw
2	Heavy Duty Torsion Bar with Bushings
3	Torsion Bar Bushing
4	Grease Fitting
5	Thrust Plate Shoulder Bolt
6	Thrust Plate Shoulder Bolt Bushing
7	Thrust Plate
8	Eye Bolt Pin
9	Split Pin
10	Bulkhead Pin
11	Split Pin
12	Eye bolt and nut
13	Heavy Duty Pushrod
14	Bushing
15	Axle Bolt
16	Axle Sleeve
17	Axle Nut
18	Load Roller Axle (includes bolt, sleeve & nut)
19	Steel Roller with Bearings
20	Washer
21	Heavy Duty Lever Arm Assembly with bushings
22	Bushing
23	Exit Roller with Bushings
24	Split Pin
25	Fork Pin

PSH-Series Frame Diagram HEAVY DUTY 3-1/4" LOW. HGT.





HERWIN, INC.
2995 CLAY PIKE
RILLTON, PA 15678
724-446-2000 1-800-868-5438
Fax: 724-446-0988
sales@herwin.biz
www.palletsmith.com

